




IMAGINATION HAS NO LIMIT VALUE UP YOUR PRODUCTS

Unrivalled Application Versatility

G4-UVF4550 SERIES delivers highly productive direct printing on the broadest range of three-dimensional applications. Customized image on metal, glass, wood, ceramic tiles, acrylic, leather, etc., can easily be produced.



Toco Image Pte Ltd

Address: 3 Tai Seng Drive, #05-01, \$535216

Tel: (65) 6281 2705


Email:sales@tocoimage.com

Features



Industrial Y Structure Frame

Constructed with industrial Y frame and structure, the machine is heavy duty and built to last.



Ricoh Gen 4 Printheads

Ricoh Gen 4 printheads provide top class durability, speed and resolution. It enables high-speed printing while easy to assemble and calibrate.



Industrial Servo Motor

A high performance of industrial servo motor provides excellent control of the movement of the shuttle.



Negative Pressure System

Negative pressure system ink supply with digital control pressure display gauges ensures high-quality printing at higher possible firing frequency, hence increasing printing speed and stability.

Technical Specification

Model: G4-UVF4550 SERIES

Print head		3 x Ricoh Gen4 industrial printhead Up to 4 x printhead (Optional)	
Structure		Industrial Structure Frame with Heavy Duty Y-Bar	
X & Y Motor		High Quality Servo Motors	
Maximum Print Size		45cm (Width) x 50cm (Length)	
Printing resolution		720x600dpi, 1200x900dpi	
Printing direction		Uni and Bi-direction	
Printing Technology		Variable Dot Printing (Grey Scale Printing)	
Media	Table. Size	46cm (Width) x 75cm (Length)	
	Max. Thickness	15cm with infrared Sensor Protection	
	Weight	15kgs	

Printing Speed

Resolution	720x600dpi	720x1200dpi	
Number of Pass	8 Pass 16 Pass		
Direction	Bi-Direction	Bi-Direction	
Speed	1'50"/ Full color A3 size	3'37"/ Full color A3 size	

Ink type	UV LED Curable Inks		
Ink Color	C, M, Y, K, White (Standard), Varnish (Optional)		
Ink Capacity	500ml Bottle		
Ink Supply System	Negative Pressure System (NPS) with Automatic Ink Supply		
UVTechnology	1 x 6 - 8W UV LED Lamp		
RIP	PhotoPrint (Bundle Version) / ColorGate (Optional)		
Interface	USB 2.0/3.0		
Power requirements	100-110Volt / 220-240V, 50/60Hz		
Assembled Dimensions (WxHxD)	128cm x 65cm x 75cm		
Net Weight	125kgs		

Inks and substrates:

Please note that properties and adhesion, weather resistance etc. of ink and substrates can vary. Please test materials before printing.

Safety notice:

You are handling with UV light source that may harm your health. Do not look directly into the UV light source nor place your hand or expose your skin directly to the UV light source.

Supplies

ITEM	ТҮРЕ	SIZE	PRODUCT RANGE
GUNSJET ULF Series	UV LED Curable Ink (Flexible/Rigid substrate)	500ml	CMYKLcLmWV
GUNSJET ULR Series	UV LED Curable Ink (Rigid Substrate)	500ml	CMYKLcLmWV
GUNSJET UV Primer	/	1L	/
GUNSJET UV Cleaner	/	1L	/